



Vertical Shaft Engines

Always monitor oil level when adding.

(See Owner's Manual for proper procedure.)

Model Name & Horsepower	Picture	Approximate Oil Capacity
<p>CLASSIC™ <i>Sprint</i>™ POWER BUILT™ CLEAN POWER™ 3.5-3.75 HP</p>		<p>20 fl oz (.59 l)</p>
<p>Quattro™ SQ Q 4.0-4.75 HP</p>		<p>20 fl oz. (.59 l)</p>
<p>EUROPA 5 HP</p>		<p>22 fl oz. (.65 l)</p>
<p>GenPower™ CLEAN POWER™ QUANTUM® QUANTUM XTE 5-6 HP</p>		<p>20 fl oz. (.59 l)</p>



Vertical Shaft Engines

Always monitor oil level when adding.

(See Owner's Manual for proper procedure.)

Model Name & Horsepower	Picture	Approximate Oil Capacity
<p>QUANTUM I/C QUANTUM XTE I/C QUANTUM.EDGE QUANTUM Diamond Plus</p> <p>5-6.5 HP</p>		<p>20 fl oz. (.59 l)</p>
<p>CLEAN TEK Pro GenTek I/C GenTek Pro</p> <p>6-6.75 HP</p>		<p>22 fl oz. (.65 l) *</p>
<p>GenPower™ INTEK INTEK Edge INTEK PRO</p> <p>6-6.75 HP</p>		<p>22 fl oz. (.65 l) *</p>
<p>GenPower™ CLEAN POWER™ POWER BUILT™</p> <p>8-11 HP</p>		<p>36 fl oz. (1.06 l)</p>
<p>INTEK™  POWER BUILT™ OHV 9-13.5 HP</p>		<p>48 fl oz. (1.42 l) *</p>

*If engine is equipped with Oil Filter, add approximately 4 oz. (.12L).

(See Owner's Manual for proper procedure.)



Vertical Shaft Engines

Always monitor oil level when adding.

(See Owner's Manual for proper procedure.)

Model Name & Horsepower	Picture	Approximate Oil Capacity
<p>CLEAN POWER™ POWER BUILT™ I/C I/C QUIET I/C Diamond Plus 12-14 HP</p>		<p>48 fl oz (1.42 l)</p>
<p>VANGUARD™ HIGH PERFORMANCE I/C (Single Cylinder) 15-16 HP</p>		<p>48 fl oz. (1.42 l) *</p>
<p>ANTI-VIBRATION AVS SYSTEM Equipped INTEK & ELS™ 13.5-17.5 HP</p>		<p>48 fl oz. (1.42 l) *</p>
<p>CLEAN TEK Pro GenTek™ Pro 15.5-17.5 HP</p>		<p>48 fl oz. (1.42 l) *</p>
<p>I/C Twin I/C Diamond Plus 18-20 HP</p>		<p>48 fl oz. (1.42 l) *</p>

*If engine is equipped with Oil Filter, add approximately 4 oz. (.12L).



(See Owner's Manual for proper procedure.)



Vertical Shaft Engines

Always monitor oil level when adding.

(See Owner's Manual for proper procedure.)

Model Name & Horsepower	Picture	Approximate Oil Capacity
<p>VANGUARD™ VTwin</p> <p>GenTek™ Pro</p> <p>PowerBull™ TWIN</p> <p>16-23 HP</p>		<p>48 fl oz. (1.42 l) *</p>
<p>GenTek™ Pro INTEK VTwin & ELS™ 22-26 HP</p>		<p>60 fl oz. (1.77 l) *</p>

*If engine is equipped with Oil Filter, add approximately 4 oz. (.12L).
(See Owner's Manual for proper procedure.)



Horizontal Shaft Engines

Always monitor oil level when adding.

(See Owner's Manual for proper procedure.)

Model Name & Horsepower	Picture	Oil Capacity
<p>VANGUARD™ 2.4 HP</p>		<p>13.5 fl oz (.4 l)</p>
<p>VANGUARD™ 4 HP</p>		<p>20 fl oz. (.59 l)</p>
<p>POWER BUILT™ I/C 3.5 Hp</p>		<p>20 fl oz. (.59 l)</p>
<p>INTEK INTEK PRO INTEK I/C INTEK SNOW™* POWER BUILT™ CLEAN POWER™ CLEAN TEK I/C OHV 5-7 HP</p>		<p>20 fl oz. (.59 l)</p> <p>*Intek Snow holds 16 fl oz. (.47 l)</p>
<p>GenTek™ Pro GenTek I/C GenPower™ GenTek™ OHV 5.5-6.5 HP</p>		<p>20 fl oz. (.59 l)</p>



Horizontal Shaft Engines

Always monitor oil level when adding.

(See Owner's Manual for proper procedure.)

Model Name & Horsepower	Picture	Oil Capacity
VANGUARD™ 6 HP		24 fl oz. (.71 l)
INTEK SNOW™ 7.5 HP		20 fl oz. (.59 l)
VANGUARD™ 7.5 HP		30 fl oz (.90 l)
GenPower™ I/C INDUSTRIAL PLUS 8-10 HP		44 fl oz. (1.3 l)
INTEK INTEK PRO INTEK I/C POWER BUILT™ GenPower™ OHV 8-11 HP		28 fl oz. (.77 l)



Horizontal Shaft Engines

Always monitor oil level when adding.

(See Owner's Manual for proper procedure.)



Model Name & Horsepower	Picture	Oil Capacity
CLEAN POWER™ CLEAN TEK Pro CLEAN TEK I/C OHV 8-11 HP		28 fl oz. (.77 l)
GenTek™ GenTek Pro GenTek I/C OHV 8-11 HP		28 fl oz. (.77 l)
VANGUARD™ 9 HP		32 fl oz. (1.2 l)
INTEKSNOW™ 9-11 HP		28 fl oz. (.77 l)
VANGUARD™ 11-13 HP		32 fl oz. (1.5 l)
I/C INDUSTRIAL PLUS 11-12 HP		48 fl oz. (1.42 l)



Horizontal Shaft Engines

Always monitor oil level when adding.

(See Owner's Manual for proper procedure.)

Model Name & Horsepower	Picture	Oil Capacity
VANGUARD™ VTwin 16-23 HP		48 fl oz. (1.42 l)*
I/C. I/C. Twin 18-19 HP		48 fl oz. (1.42 l)*
••FOURCE•• .75-1 HP		3.0 fl oz. (80ml)
5hp 4 CYCLE Outboard		24 fl oz. (.71 l)

*If engine is equipped with Oil Filter, add approximately 4 oz. (.12L).
(See Owner's Manual for proper procedure.)