




 DANA CORPORATION
 FREDERICKTOWN, OHIO
 4360-76
 NOMA OUTDOOR PRODUCTS 316512

DANA CORPORATIONSERVICE PARTS REPLACEMENT LISTINGMODEL NO.: 4360-76DATE: 10-29-93DESCRIPTION: FIVE SPEED LINEAR SHIFT TRANSAXLECUSTOMER & PART NO.: NOMA OUTDOOR PRODUCTS, INC. - 316512

| <u>KEY</u> <u>NO.</u> | <u>DANA</u> <u>PART NO.</u> | <u>NOMA</u> <u>PART NO.</u> | <u>NO.</u> <u>REQ'D.</u> | <u>DESCRIPTION</u> |
|--------------------------|--------------------------------|--------------------------------|-----------------------------|-----------------------------------|
| 1 | 5305-D | | 1 | Housing, Upper |
| 2 | 1919 | | 14 | Screw, Tapping, 1/4-20 X .734 Lg. |
| 3 | 5112 | | 2 | Ball, Detent |
| 4 | 3626 | | 2 | Spring, Detent |
| 5 | 3623 | | 2 | Screw, Set |
| 6 | 4731 | | 1 | Kit, Shifter, Ass'y. |
| 7 | 5024 | | 1 | Boot, Shifter |
| 8 | 5016 | | 1 | Spacer, .781 X 1.00 X .494 |
| 9 | 5018 | | 1 | Spacer, .604 X 1.17 X .394 |
| 10 | 1106 | | 1 | Ring, Retaining |
| 11 | 4689 | | 4* | Ass'y., Kit, Shim, .625 Shaft |
| 12 | 3907 | | 1 | Puck, Friction |
| 13 | 3876 | | 2 | Washer, Plain, .632 X 1.38 X .046 |
| 14 | 1746 | | 1 | Key, Woodruff, #9 |
| 15 | 4551 | | 1 | Ass'y., Kit, Input Shaft |
| 16 | 3590 | | 1 | Pinion, Bevel, 14T. |
| 17 | 3624 | | 1 | Ring, Retaining |
| 18 | 1090 | | 1 | Chain, 22 Pitches |
| 19 | 1542 | | 3 | Bearing, Flange |
| 20 | 5402 | | 1 | Gear, Spur, 14T. |
| 21 | 5303 | | 1 | Collar, Clutch |
| 22 | 4758 | | 1 | Ass'y., Kit, Clutch Keys |
| 23 | 5416 | | 1 | Seal, Oil |
| 24 | 5403 | | 1 | Shaft, Intermediate |
| 25 | 1375 | | 1 | Key, Woodruff, #61 |
| 26 | 3627 | | 1 | Ring, Retaining |
| 27 | 3897 | | 1 | Sprocket, 14T. |
| 28 | 3841 | | 1 | Spacer |
| 29 | 4831 | | 1 | Ass'y, Kit, Gear Set, 15T. & 35T. |
| 30 | 5014 | | 1 | Gear, Spur, 27T. |
| 31 | 3783 | | 1 | Gear, Spur, 25T. |
| 32 | 3869 | | 1 | Gear, Spur, 22T. |
| 33 | 3817 | | 1 | Gear, Spur, 20T. |
| 34 | 5027 | | 1 | Spacer, 1.133 X 1.50 X .374 |
| 35 | 3628 | | 1 | Washer, Plain, .640 X 1.37 X .061 |
| 36 | 1423 | | 2 | Washer, Plain, .632 X 1.00 X .026 |
| 37 | 3422 | | 1 | Spacer, .630 X 1.00 X .169 |
| 38 | 4286 | | 1 | Ass'y., Gear, Comb., 12T. & 35T. |
| 39 | 3967 | | 1 | Shaft, Idler |

Model #4360-76

Page 2

| <u>KEY</u> <u>NO.</u> | <u>DANA</u> <u>PART NO.</u> | <u>NOMA</u> <u>PART NO.</u> | <u>NO.</u> <u>REQ'D.</u> | <u>DESCRIPTION</u> |
|--------------------------|--------------------------------|--------------------------------|-----------------------------|------------------------------------|
| 40 | 3630 | | 1 | Spacer, .781 X 1.00 X .281 |
| 41 | 3815 | | 1 | Sprocket, 10T. |
| 42 | 5012 | | 1 | Gear, Bevel, 42T. |
| 43 | 4691 | | 1* | Ass'y., Kit, Shim, .750 Shaft |
| 44 | 5015 | | 1 | Shaft, Drive |
| 45 | 4831 | | 1 | Ass'y, Kit, Gear Set, 15T. & 35T. |
| 46 | 5013 | | 1 | Gear, Spur, 23T. |
| 47 | 3719 | | 1 | Gear, Spur, 25T. |
| 48 | 3868 | | 1 | Gear, Spur, 28T. |
| 49 | 3818 | | 1 | Gear, Spur, 30T. |
| 50 | 3714 | | 1 | Spacer, .781 X 1.00 X .375 |
| 51 | 1145 | | 1 | Washer, Plain, .632 X 1.00 X .060 |
| 52 | 5130 | | 2 | Washer, Neoprene |
| 53 | 3184 | | 2 | Washer, Plain, .758 X 1.25 X .031 |
| 54 | 3880 | | 1 | Axle, L.H. |
| 55 | 3780 | | 2 | Gear, Miter, 15T. |
| 56 | 3656 | | 2 | Ring, Retaining |
| 57 | 3839 | | 1 | Gear, Spur, 32T. |
| 58 | 3919 | | 1 | Shaft, Cross |
| 59 | 3781 | | 2 | Gear, Miter, 15T. |
| 60 | 3881 | | 1 | Axle, R.H. |
| 61 | 5304-F | | 1 | Housing, Lower |
| 62 | 3920 | | 1 | Puck, Friction |
| 63 | 3276 | | 1 | Disc, Brake |
| 64 | 3758 | | 1 | Spacer |
| 65 | 3916 | | 1 | Jaw, Brake |
| 66 | 3843 | | 2 | Pin, Dowel |
| 67 | 5120 | | 1 | Screw, Tapping, 5/16-18 X 2.25 Lg. |
| 68 | 5283 | | 1 | Lever, Actuating |
| 69 | 3760 | | 2 | Washer, Plain, .321 X 1.00 X .055 |
| 70 | 3917 | | 1 | Bracket, Anti-Rotation |
| 71 | 3847 | | 1 | Nut, Lock, 5/16-24 |
| 72 | 3724 | | 1 | Screw, Tapping, 5/16-18 X 1.44 Lg. |
| 73 | 5131 | | 2 | Screw, Tapping w/Sealer |
| 74 | 4300 | | 1 | Grease |
| 75 | 5415 | | 1 | Bearing, Flange |

* Use in various combinations to maintain proper clearances.

** Order Key No. 15.