





 DANA CORPORATION

 FREDERICKTOWN, OHIO

 MURRAY OHIO MFG. CO.

 4360-85

DANA CORPORATIONSERVICE PARTS REPLACEMENT LISTINGMODEL NO.: 4360-85DATE: 2-17-94DESCRIPTION: FIVE SPEED LINEAR SHIFT TRANSAXLECUSTOMER & PART NO.: THE MURRAY OHIO MANUFACTURING CO. - #

<u>KEY NO.</u>	<u>DANA PART NO.</u>	<u>MURRAY PART NO.</u>	<u>NO. REQ'D.</u>	<u>DESCRIPTION</u>
1	5305-D		1	Housing, Upper
2	1919	407185	14	Screw, Tapping, 1/4-20 X .734 Lg.
3	5112		2	Ball, Detent
4	3626		2	Spring, Detent
5	3623		2	Screw, Set
6	4794		1	Ass'y., Kit, Shifter
7	5024		1	Boot, Shifter
8	3907		1	Puck, Friction
9	5131		2	Screw, Tapping, w/Sealer
10	1106		1	Ring, Retaining
11	4689		3*	Ass'y., Kit, Shim, .625 Shaft
12	5415		1	Bearing, Flange
13	3876		2	Washer, Plain, .632 X 1.38 X .046
14	1746		1	Key, Woodruff, #9
15	4551		1	Ass'y., Kit, Input Shaft
16	3590		1	Pinion, Bevel, 14T.
17	3624		1	Ring, Retaining
18	3625		1	Chain, 24 Pitches
19	1542		3	Bearing, Flange
20	5402		1	Gear, Spur, 14T.
21	5467		1	Collar, Clutch
22	4759		1	Ass'y., Kit, Clutch Keys
23	5202		1	Gear, Spur, 19T.
24	5403		1	Shaft, Intermediate
25	1375	400061	1	Key, Woodruff, #61
26	3627		1	Ring, Retaining
27	3830		1	Sprocket, 18T.
28	3841		1	Spacer
29	5365		1	Gear, Spur, 37T.
30	3867		1	Gear, Spur, 30T.
31	3783		1	Gear, Spur, 25T.
32	3869		1	Gear, Spur, 22T.
33	5027		1	Spacer, 1.133 x 1.50 x .374
34	3724		1	Screw, Tapping, 5/16-18 x 1.44 Lg.
35	3628		1	Washer, Plain, .640 X 1.37 X .061
36	1423	400073	2	Washer, Plain, .632 X 1.00 X .026
37	3422		1	Spacer, .630 X 1.00 X .169
38	4286		1	Ass'y., Gear, Comb., 12T. & 35T.
39	3967		1	Shaft, Idler

Model #4360-85

Page 2

<u>KEY NO.</u>	<u>DANA PART NO.</u>	<u>MURRAY PART NO.</u>	<u>NO. REQ'D.</u>	<u>DESCRIPTION</u>
40	3901		1	Spacer, .635 X .875 X .755
41	3645		1	Sprocket, 9T.
42	3853		1	Gear, Bevel, 42T.
43	4691		2*	Ass'y., Kit, Shim, .750 Shaft
44	3882		1	Shaft, Drive
45	5364		1	Gear, Spur, 12T.
46	3866		1	Gear, Spur, 20T
47	3719		1	Gear, Spur, 25T.
48	3868		1	Gear, Spur, 28T.
49	3683		1	Gear, Spur, 31T.
50	3714		1	Spacer, .781 X 1.00 X .375
51	1145	400040	1	Washer, Plain, .632 X 1.00 X .060
52	5130		2	Washer, Neoprene
53	3184		2	Washer, Plain, .758 X 1.25 X .031
54	3923		1	Axle, L.H.
55	3780		2	Gear, Miter, 15T.
56	3656		2	Ring, Retaining
57	3839		1	Gear, Spur, 32T.
58	3919		1	Shaft, Cross
59	3781		2	Gear, Miter, 15T.
60	3924		1	Axle, R.H.
61	5304-F		1	Housing, Lower
62	3920		1	Puck, Friction
63	3276	407257	1	Disc, Brake
64	3758		1	Spacer
65	3916		1	Jaw, Brake
66	3843		2	Pin, Dowel
67	5120		1	Screw, Tapping, 5/16-18 X 2.25 Lg.
68	5286		1	Lever, Actuating
69	3760		1	Washer, Plain, .321 X 1.00 X .055
70	3917		1	Bracket, Anti-Rotation
71	3847		1	Nut, Lock, 5/16-24
72	5416		1	Seal, Oil
73	4300		1	Grease

* Use in various combinations to maintain proper clearances.

** Order Key No. 15.