



DANA CORPORATION 4900-3
 FREDERICKTOWN, OHIO
 MURRAY OHIO MFG. CO. #093264



DANA CORPORATION

SERVICE PARTS REPLACEMENT LISTING

MODEL NO.: 4900-3

DATE: 11-17-93

DESCRIPTION: HYDROSTATIC TRANSAXLE

CUSTOMER & PART NO.: MURRAY OHIO MANUFACTURING CO. - #093264

| <u>KEY</u> <u>NO.</u> | <u>DANA</u> <u>PART NO.</u> | <u>MURRAY</u> <u>PART NO.</u> | <u>NO.</u> <u>REQ'D.</u> | <u>DESCRIPTION</u> |
|--------------------------|--------------------------------|----------------------------------|-----------------------------|-----------------------------------|
| 1 | 5351-BC | | 1 | Housing, Upper |
| 2 | 3789 | | 1 | V-Ring |
| 3 | 1919 | | 16 | Screw, Tapping, 1/4-20 x .734 |
| 4 | 4821 | | 1 | Ass'y., Shaft & Cam |
| 5 | 3758 | | 2 | Spacer |
| 6 | 5338 | | 2 | Puck, Friction |
| 7 | 5336 | | 1 | Nut, Locking, Jam |
| 8 | 5337 | | 1 | Stud, Adjustment |
| 9 | 3884 | | 1 | O-Ring |
| 10 | 5356 | | 1 | Key, Drive |
| 11 | 4820 | | 3 | Ass'y., Bearing |
| 12 | 3890 | | 1 | Washer, Plain, .505 x .942 x .040 |
| 13 | 5357 | | 1 | Shaft, Input |
| 14 | 5339 | | 1 | Disc, Brake |
| 15 | 5180 | | 2 | Gear, Spur, 10T. |
| 16 | 4690 | | 2* | Ass'y., Kit, Shim, .500 Shaft |
| 17 | 4819 | | 1 | Ass'y., Bearing |
| 18 | 5353 | | 1 | Shaft, Idler |
| 19 | 1068 | | 1 | Washer, Plain, .632 x 1.00 x .041 |
| 20 | 3471 | | 1 | Spacer, .630 x 1.00 x .549 |
| 21 | 5349 | | 1 | Gear, Spur, 41T. |
| 22 | 5130 | | 2 | Washer, Neoprene |
| 23 | 3184 | | 2 | Washer, Plain, .758 x 1.25 x .031 |
| 24 | 5172 | | 1 | Axle, L.H. |
| 25 | 3871 | | 2 | Gear, Miter, 15T. |
| 26 | 3656 | | 2 | Ring, Retaining |
| 27 | 5181 | | 1 | Gear, Spur, 41T. |
| 28 | 3726 | | 2 | Gear, Miter, 15T. |
| 29 | 3919 | | 1 | Shaft, Cross |
| 30 | 5173 | | 1 | Axle, R.H. |
| 31 | 4691 | | 1* | Ass'y., Kit, Shim, .750 Shaft |

Model #4900-3

Page 2

| <u>KEY</u> <u>NO.</u> | <u>DANA</u> <u>PART NO.</u> | <u>MURRAY</u> <u>PART NO.</u> | <u>NO.</u> <u>REQ'D.</u> | <u>DESCRIPTION</u> |
|--------------------------|--------------------------------|----------------------------------|-----------------------------|-------------------------------|
| 32 | 5350-A | | 1 | Housing, Lower |
| 33 | 5366 | | 1 | Ring, Retaining |
| 34 | 3306 | | 4 | Screw, Tapping, #10-24 x 1.05 |
| 35 | 5368 | | 1 | Pulley, 4.75 Dia. |
| 36 | 5412 | | 1 | Hub |
| 37 | 5413 | | 1 | Fan |
| 38 | 5414 | | 1 | Ring, Clamp |
| 39 | 5376 | | 1 | Hst, CCW Control Rotation |
| 40 | 1375 | | 1 | Key, Woodruff, #61 |
| 41 | 4300 | | 1 | Grease |

* Use in various combinations to maintain proper clearances.

** Silicone Sealant to be applied between Upper and Lower Housings (use Loctite Ultra Gray Silicone 5699 or equivalent).

NOTE: Transaxle Assembly without Key No. 39 is available as Part No. 4885.