



For Husqvarna Parts Call 606-678-9623 or 606-561-4983



SERVICE			<b>14</b>
			I0300147

IPL, Technical Specification 2003, 2003-09, 106 24 61-66

# Technical Specification 2003

**Hedge trimmers, Ice augers, Blowers,  
Pole saws, Pole hedge trimmers**

106 24 61-66



	Displacement Hubraum Cylindrie Cilindrada Slagvolyv	Bore Bohrung Aksage Diametro de cilindro Cylinderdiameter	Stroke Hub Course Carrera Slaglängd	Max power of speed Höchstleistung bei Puissance max. à Potencia máxima a Max effekt vid	Idling speed Leerlaufdrehzahl Régime de ralenti Régimen de ralentí Tomgångsvarvtal	Engagement Eingriffsdrhzahl Régime d'embrayage Régimen de acoplamiento Ingreppsvarvtal	No load free speed Höchstzahl Nombre de tours max. A maxima revolución Max ** rpm	Spark plug Zündkerze Bougie Tändstift	Electrode gap Elektrodenabstand Ecartement des électrodes Distancia entre electrodos Elektodavstånd	Ignition system Zündanlage Système d'allumage Carburador y reglaje encendido Tändsystem	Air gap Luftspalt Ecartement Distancia Luftgap	Type of carburetor and setting Vergaserart und Einstellung Carburateur et réglage Carburador y reglaje Förgasartyp och inställning		Fuel tank volume Füllmenge des Kraftstofftanks Débit du réservoir de carburant Capacidad del tanque de combustible Tankvolyv bränsle	Weight Gewicht Poids Vikt	Angel gear reduction Untersätzung des Vinkelgetriebes Demultiplication du carter de renvoi Desmultiplicación Utväxlingsförhållande	Blade speed Klingengeschwindigkeit Vitesse de la lame Velocidad de cuchilla Knivhastighet	Air volume Luftvolumenstrom Volume flux d'air Caudal de aire Luftvolyvström	Air velocity Luftgeschwindigkeit Vitesse d'air Velocidad Luftastighet
	cc	Ø mm	mm	kW(HP) rpm	rpm	rpm	rpm	mm inch	type	mm inch	type	set *	liters	kg		klipp/min	m3/h	km/h	
<b>323P4</b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	3 700	11 000-** 11 700	NGK BPMR 7A	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 12	H=2* L=1	0.50	5.0	1:1	—	—	
<b>325P5<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	3 700	11 000-** 11 700	NGK BPMR 7A	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 12	H=2* L=1	0.50	5.9	1:1	—	—	
<b>E-tech II 326P4</b>	24.5	34.0	27.0	0.9 (1.2) 8 400	2 700	3 700	11 000-** 11 700	Champion RCJ 6Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 12	H=2** L=1**	0.50	5.4	1:1	—	—	
<b>E-tech II 326P5<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 8 400	2 700	3 700	11 000-** 11 700	Champion RCJ 6Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 12	H=2** L=1**	0.50	6.2	1:1	—	—	
<b>323HD60</b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	4 500	11 000-** 12 600	Champion RCJ 7Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2* L=1	0.50	5.6	1:4.90	4694	—	
<b>325HD60<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	4 500	11 000-** 12 600	Champion RCJ 7Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2* L=1	0.50	5.6	1:4.90	4694	—	
<b>325HD75<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	4 500	11 000-** 12 600	Champion RCJ 7Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2* L=1	0.50	5.9	1:4.90	4694	—	
<b>E-tech II 326HD60<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 8 400	2 700	4 500	11 000-** 12 600	Champion RCJ 6Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2** L=1**	0.50	5.7	1:4.90	4694	—	
<b>E-tech II 326HD75<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 8 400	2 700	4 500	11 000-** 12 600	Champion RCJ 6Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2** L=1**	0.50	6.0	1:4.90	4694	—	
<b>325HDA55<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	5 200	9 500-** 10 500	NGK BPMR 7A	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2* L=1	0.50	5.5	1:4.78	4184	—	
<b>E-tech II 326HDA55<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 8 400	2 700	5 200	9 500-** 10 500	Champion RCJ 6Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2** L=1**	0.50	5.8	1:4.78	4184	—	
<b>325HE3<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	5 200	9 500-** 10 500	NGK BPMR 7A	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2* L=1	0.50	5.7	1:4.78	4184	—	
<b>325HE4<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	5 200	9 500-** 10 500	NGK BPMR 7A	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2* L=1	0.50	5.8	1:4.78	4184	—	
<b>E-tech II 326HE3<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 8 400	2 700	5 200	9 500-** 10 500	Champion RCJ 6Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2** L=1**	0.50	6.0	1:4.78	4184	—	
<b>E-tech II 326HE4<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 8 400	2 700	5 200	9 500-** 10 500	Champion RCJ 6Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2** L=1**	0.50	6.1	1:4.78	4184	—	
<b>325HS75<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	4 500	11 000-** 12 600	Champion RCJ 7Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2* L=1	0.50	5.5	1:4.90	4694	—	
<b>325HS99<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 9 000	2 700	4 500	11 000-** 12 600	Champion RCJ 7Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2* L=1	0.50	5.8	1:4.90	4694	—	
<b>E-tech II 326HS75<sub>X-SERIES</sub></b>	24.5	34.0	27.0	0.9 (1.2) 8 400	2 700	4 500	11 000-** 12 600	Champion RCJ 6Y	0.5 0.02	WALBRO CD	0.3 0.012	ZAMA C1Q EL 14	H=2** L=1**	0.50	5.6	1:4.90	4694	—	
<b>225 AI 15</b>	26.9	35.0	28.0	0.9 (1.2) 9 000	2 700	3 700	11 000-** 11 500	Champion RCJ 7Y	0.5 0.02	WALBRO CD	0.3 0.012	WALBRO WT 500B	H=1* L=1*	0.40	5.3	1:22	—	—	
<b>225 AI 25</b>	26.9	35.0	28.0	0.9 (1.2) 9 000	2 700	3 700	11 000-** 11 500	Champion RCJ 7Y	0.5 0.02	WALBRO CD	0.3 0.012	WALBRO WT 500B	H=1* L=1*	0.40	5.8	1:59	—	—	
<b>141B</b>	40.2	40.0	32.0	1.9 (2.6) 7 500	2 500	—	7 500	NGK BPM R7A	0.6 0.024	ET	0.4 0.016	WALBRO WYK	H=FIXED L=FIXED	1.60	9.0	—	—	560 230	
<b>155B</b>	48.7	44.0	32.0	2.2 (3.0) 7 800	2 500	—	7 800	NGK BPM R7A	0.6 0.024	ET	0.4 0.016	WALBRO WYK	H=FIXED L=FIXED	2.10	10.2	—	—	670 250	
<b>225B</b>	26.9	35.0	28.0	0.9 (1.2) 9 000	2 700	—	7 900	Champion RCJ 7Y	0.5 0.02	WALBRO CD	0.3 0.012	WALBRO WT 500B	H=1* L=1*	0.40	5.1	—	—	500 300	
<b>225B<sub>X-SERIES</sub></b>	26.9	35.0	28.0	0.9 (1.2) 9 000	2 700	—	7 900	Champion RCJ 7Y	0.5 0.02	WALBRO CD	0.3 0.012	WALBRO WT 500B	H=1* L=1*	0.40	5.3	—	—	500 300	

◇ Do not exceed the max no load free speed or engine damage may occur. This figure is for broken in unit. Reduce rpm by 600-700 rpm for a new product. 106 23 62-73

\*Basic setting. Only applies to needles without caps fitted.

\*\*Regulated ignition system.

# Technical Specification 2003

## Hedge trimmers, Ice augers, Blowers, Pole saws, Pole hedge trimmers