



DANA CORPORATION  
FREDERICKTOWN, OHIO 2000-10  
MURRAY OHIO MANUFACTURING CO.

DANA CORPORATIONSERVICE PARTS REPLACEMENT LISTING

MODEL NO.: 2000-10

DATE: 7-22-92

DESCRIPTION: FIVE SPEED LINEAR SHIFT TRANSAXLECUSTOMER & PART NO.: MURRAY OHIO MANUFACTURING CO. - #

<u>KEY NO.</u>	<u>DANA PART NO.</u>	<u>MURRAY PART NO.</u>	<u>NO. REQ'D.</u>	<u>DESCRIPTION</u>
1	5151-B		1	Housing, Upper
2	1919	407185	13	Screw, Tapping, 1/4-20 x .734 Lg.
3	5112		2	Ball, Detent
4	5185		2	Spring, Detent
5	5184		1	Cover, Detent
6	3035	407268	2	Screw, Tapping, #8-32 x .50 Lg.
7	1099	400035	1	Ring, Retaining
8	4689		1*	Ass'y., Kit, Shim, .625 Shaft
9	3876		1	Washer, Plain, .632 x 1.38 x .046
10	1374	400060	1	Key, Woodruff, #9
11	4687		1	Ass'y., Kit, Input Shaft
12	3936		1	Pinion, Bevel, 13T.
13	3956		1	Ring, Retaining
14	4719		1	Ass'y., Shifter
15	5196		1	Seal
16	4690		1*	Ass'y., Kit, Shim, .500 Shaft
17	3631		1	Collar, Clutch
18	4688		1	Ass'y., Kit, Clutch Keys
19	5165		1	Shaft, Drive
20	3627		1	Ring, Retaining
21	5155		1	Gear, Spur, 20T.
22	5154		1	Gear, Spur, 32T.
23	5239		1	Spacer, 1.130 x 1.330 x .465
24	5152		1	Gear, Spur, 24T.
25	5149		1	Gear, Spur, 20T.
26	5148		1	Gear, Spur, 17T.
27	5238		1	Gear, Bevel, 39T. & Spur, 15T.
28	5201		1	Washer, Plain, 1.135 x 1.56 x .062
29	5183		1	Bearing, Flange
30	5180		1	Gear, Spur, 10T.
31	5182		1	Bearing, Flange
32	5258		1	Seal
33	3887		1	Washer, Plain, .505 x .942 x .015
34	4729		1	Ass'y., Kit, Cone Brake
35	4692		1*	Ass'y., Kit, Shim, .464 Shaft
36	5251		1	Klip Ring
37	5130		2	Washer, Neoprene
38	3180		1	Washer, Plain, .758 x 1.25 x .062
39	5160		1	Gear, Spur, 12T.

Model #2000-10  
Page 2

<u>KEY</u> <u>NO.</u>	<u>DANA</u> <u>PART NO.</u>	<u>MURRAY</u> <u>PART NO.</u>	<u>NO.</u> <u>REQ'D.</u>	<u>DESCRIPTION</u>
40	3983		1	Gear, Spur, 20T.
41	5163		1	Gear, Spur, 24T.
42	5162		1	Gear, Spur, 26T.
43	5240		1	Spacer, 1.710 x 1.910 x .375
44	5161		1	Gear, Spur, 29T.
45	3955		1	Washer, Plain, .758 x 1.88 x .062
46	5172		1	Axle, L.H.
47	3184		2	Washer, Plain, .758 X 1.25 X .031
48	3780		2	Gear, Miter, 15T.
49	3656		2	Ring, Retaining
50	5181		1	Gear, Spur, 41T.
51	3919		1	Shaft, Cross
52	3781		2	Gear, Miter, 15T.
53	4691		1*	Ass'y., Kit, Shim, .750 Shaft
54	5173		1	Axle, R.H.
55	5150-A		1	Housing, Lower
56	3396		1	Screw, Tapping, 1/4-20 x .875 Lg.
57	3987		1	Shaft, Idler
58	3888		1	Washer, Plain, .505 x .942 x .020
59	5293		1	Gear, Spur, 10T.
60	3789		1	Seal, V-Ring
61	4300		1	Grease

\* Use in various combinations to maintain proper clearances.

\*\* Order Key Number 11.