



BUNTON

DANA CORPORATION
 FREDERICKTOWN, OHIO
 4360-95

DANA CORPORATIONSERVICE PARTS REPLACEMENT LISTINGMODEL NO.: 4360-95DATE: 8-4-94DESCRIPTION: FIVE SPEED LINEAR SHIFT TRANSAXLECUSTOMER & PART NO.: BUNTON - #

<u>KEY</u> <u>NO.</u>	<u>DANA</u> <u>PART NO.</u>	<u>BUNTON</u> <u>PART NO.</u>	<u>NO.</u> <u>REQ'D.</u>	<u>DESCRIPTION</u>
1	5305-E		1	Housing, Upper
2	1919		16	Screw, Tapping, 1/4-20 X .734 Lg.
3	5112		2	Ball, Detent
4	3626		2	Spring, Detent
5	3623		2	Screw, Set
6	4604		1	Kit, Shifter Ass'y.
7	5024		1	Boot, Shifter
8	1106		1	Ring, Retaining
9	4689		4*	Ass'y., Kit, Shim, .625 Shaft
10	3876		2	Washer, Plain, .632 X 1.38 X .046
11	1746		1	Key, Woodruff, #9
12	4559		1	Ass'y., Kit, Input Shaft
13	3590		1	Pinion, Bevel, 14T.
14	3624		1	Ring, Retaining
15	5510		3	Bearing, Flange
16	5402		1	Gear, Spur, 14T.
17	5303		1	Collar, Clutch
18	4760		1	Ass'y., Kit, Clutch Keys
19	5511		1	Bearing, Flange
20	5404		1	Shaft, Intermediate
21	3627		1	Ring, Retaining
22	3830		1	Sprocket, 18T.
23	3841		1	Spacer, 1.134 X 1.45 X .494
24	5407		1	Gear, Spur, 35T.
25	3867		1	Gear, Spur, 30T.
26	3783		1	Gear, Spur, 25T.
27	3869		1	Gear, Spur, 22T.
28	5027		1	Spacer, 1.133 X 1.50 X .374
29	3628		1	Washer, Plain, .640 X 1.37 X .061
30	1423		2	Washer, Plain, .632 X 1.00 X .026
31	3422		1	Spacer, .630 X 1.00 X .169
32	4286		1	Ass'y., Gear, Comb., 12T. & 35T.
33	3967		1	Shaft, Idler
34	5012		1	Gear, Bevel, 42T.
35	3630		3	Spacer, .781 X 1.00 X .281
36	3714		3	Spacer, .781 X 1.00 X .375
37	5015		1	Shaft, Drive
38	5406		1	Gear, Spur, 15T.
39	3866		1	Gear, Spur, 20T.

Model #4360-95

Page 2

<u>KEY NO.</u>	<u>DANA PART NO.</u>	<u>BUNTON PART NO.</u>	<u>NO. REQ'D.</u>	<u>DESCRIPTION</u>
40	3719		1	Gear, Spur, 25T.
41	3868		1	Gear, Spur, 28T.
42	1145		1	Washer, Plain, .632 X 1.00 X .060
43	5130		2	Washer, Neoprene
44	3198		1	Washer, Plain, .758 X 1.25 X .040
45	5031		1	Ring, Retaining
46	3839		1	Gear, Spur, 32T.
47	5032		1	Cross, Axle
48	5513		1	Axle
49	1375		2	Key, Woodruff, #61
50	3180		1	Washer, Plain, .758 X 1.25 X .062
51	4691		1*	Ass'y., Kit, Shim, .750 Shaft
52	5304-E		1	Housing, Lower
53	5016		1	Spacer, .781 x 1.00 x .494
54	5508		1	Seal, Oil
55	3734		2	Washer, Plain, .758 X 1.25 X .045
56	3625		1	Chain, 24 Pitches
57	3645		1	Sprocket, 9T.
58	3683		1	Gear, Spur, 31T.
59	5267		1	Switch, Neutral
60	5202		1	Gear, Spur, 19T.
61	4300		1	Grease

* Use in various combinations to maintain proper clearances.

** Order Key No. 12.

*** Silicone Sealant to be applied between Upper and Lower Housings (use Loctite Ultra Gray Silicone 5699 or equivalent).