For Husqvarna Parts Call 606-678-9623 or 606-561-4983

All models of trimmers, clearing saws, back pack brushcutters, pruners, edgers, hedgetrimmers

Poster "Technical specification" 1997

The “Technical specification“ plate for trimmers, clearing saws, back pack brushcutters, pruners, edgers and hedgetrimmers has now been updated for 1997 models.

New ref. no.	Description
106 23 62-64	Poster "Technical specification 1997"

TECHNICAL SPECIFICATION 1997

Husqvarna Trimmers, Brush cutters, Back pack, Pruners, Edger, Hedgetrimmers

Husqvarna

	Displacement Cylinder volume Cylindrée Hubraum cc	Bore Alésage Bohrung Diamètre de cylindre Cylinderdiameter mm	Stroke Course Hub Carrera Slagtoppl mm	Max power of speed Maximum speed for Puissance maximale Puissance maximale Max effekt at kW (HP) rpm	Idling speed Régime de ralenti Leerlaufdrehzahl Régimen de ralentí Regimen de ralentí Tomgangsvarvtal rpm	Engagement Régime d'embrayage Kupplungsdrehzahl Régimen de acoplamiento Regimen de acoplamiento Inkopplingsvarvtal rpm	No load free speed Vitesse maximale Leerlaufdrehzahl Régimen de vacío Regimen de vacío Max varvtal rpm ◊	Spark plug Bougie Zündkerze Bujía Tändstift	Electrode gap Distance entre les électrodes Elektrodenabstand Distancia entre electrodos Avstånd mellan elektroderna Elektrodavstand mm/inch	Ignition system Système de allumage Zündsystem Sistema de encendido Tändsystem	For gap Jeu Luftspalt Distancia Avstånd mm/inch	Carburettor Carburateur Vergaser Carburador Förgasare type	set *	Fuel tank volume Réservoir des carburant Kraftstofftank Depósito de combustible Bränsletank Capacidad del tanque de combustible Tankvolym Lit.	Weight Poids Gewicht Peso Vikt kg	Angle gear reduction Démultiplication Winkelgetriebe Desmultiplicación angular Vinkelgiftreforhållande	Shaft thread Filetage de l'arbre Welle Gewinde Rosca del eje Axelgänga	Blade hole diameter Diamètre du trou de la lame Durchmesser der Sägeblattbohrung Diámetro del agujero central de la hoja Klingborrdiameter mm	Blade diameter Diamètre de la lame Sägeblattdurchmesser Diámetro de la hoja Klingdiameter mm	Angle Inclinaison Angle Ángulo Vinkel deg	Max shaft speed Vitesse maximale du moteur Max. Drehzahl Velocidad máx. de la Max varvtal rpm
Mondo	24,0	34,5	26,4	0,5 (0,7) 7.600	3.000	4.000	9.000	Champion RCJ8Y NGK BPM 6A	0,5/0,02	Phelon CD	0,3/0,012	Walbro WT 380	H=2 L=2	0,48	4,3	1:1	3/8"x24(R)	_	_	30°	9.000
122L	22,5	32,0	28,0	0,7 (0,9) 7.500	3.000	3.900	10.800	NGK BPM 6Y	0,6/0,024	Ikeda Denso Solid State	0,3/0,012	Walbro WYL	– –	0,40	4,4	1:1,33	M10x1,25	_	_	35°	8.100
Mondo Max	24,0	34,5	26,4	0,5 (0,7) 7.600	3.000	4.000	9.000	Champion RCJ 8Y	0,5/0,02	Phelon CD	0,3/0,012	Walbro WT 380	H=2 L=2	0,48	4,8	1:1,23	3/8"x24(L)	_	_	30°	7.300
225L/LD	25,4	34,0	28,0	0,9 (1,2) 9.000	2.700	3.700	11.000-12.000	Champion RCJ 7Y	0,5/0,02	Walbro CD	0,3/0,012	Walbro WT 235 Walbro WT 270	H=1–1 1/4 L=1–1 1/4	0,50	L: 5,7 LD: 6,0	1:1,40	M10x1,25	_	_	35°	8.500
232L	30,8	35,0	32,0	1,1 (1,5) 8.400	2.700	3.800	11.000-12.000	Champion RCJ 7Y	0,5/0,02	Walbro CD	0,3/0,012	Walbro WT 235 Walbro WT 270	H=1–1 1/4 L=1–1 1/4	0,50	6,2	1:1,40	M10x1,25	_	_	35°	8.500
Mondo Mega	24,0	34,5	26,4	0,5 (0,7) 7.600	3.000	4.000	9.000	Champion RCJ 8Y	0,5/0,02	Phelon CD	0,3/0,012	Walbro WT 380	H=2 L=2	0,46	6,2	1:1,33	3/8"x24(L)	20,0	200	30°	7.300
225R/RD	25,4	34,0	28,0	0,9 (1,2) 9.000	2.700	3.700	11.000-12.000	Champion RCJ 7Y	0,5/0,02	Walbro CD	0,3/0,012	Walbro WT 235 Walbro WT 270	H=1–1 1/4 L=1–1 1/4	0,50	R: 6,0 RD: 6,3	1:1,40	M10x1,25	20,0	200-255	35°	8.500
232R	30,8	35,0	32,0	1,1 (1,5) 8.400	2.700	3.800	11.000-12.000	Champion RCJ 7Y	0,5/0,02	Walbro CD	0,3/0,012	Walbro WT 235 Walbro WT 270	H=1–1 1/4 L=1–1 1/4	0,50	6,5	1:1,40	M10x1,25	20,0	200-275	35°	8.500
235R	36,3	38,0	32,0	1,3 (1,7) 9.000	2.700	3.800	11.000-12.000	Champion RCJ 7Y	0,5/0,02	Walbro CD	0,3/0,012	Walbro WT 235 Walbro WT 270	H=1–1 1/4 L=1–1 1/4	0,50	7,3	1:1,53	M12x1,75	20,0	200-300	35°	7.800
240R	40,2	40,0	32,0	1,8 (2,4) 9.000	2.700	3.700	12.500	Champion RCJ 7Y	0,5/0,02	Electrolux ET	0,3/0,012	Walbro WT 99	H=1–1 1/4 L=1–1 1/4	0,80	8,6	1:1,36	M12x1,75	20,0	200-300	30°	9.190
245R	44,3	42,0	32,0	2,0 (2,7) 9.000	2.700	3.700	12.500	Champion RCJ 7Y	0,5/0,02	Electrolux ET	0,3/0,012	Walbro WT 99	H=1–1 1/4 L=1–1 1/4	0,80	8,6	1:1,36	M12x1,75	20,0	200-300	30°	9.190
250R	48,7	44,0	32,0	2,1 (2,8) 9.000	2.700	4.300	12.500	Champion RCJ 7Y	0,5/0,02	Electrolux ET	0,3/0,012	Walbro HDA 86B Walbro HDA 142	H=1–1 1/4 L=1–1 1/4	0,80	9,2	1:1,36	M12x1,75	20,0	200-300	30°	9.190
245RX	44,3	42,0	32,0	2,0 (2,7) 9.000	2.700	3.700	12.500	Champion RCJ 7Y	0,5/0,02	Electrolux ET	0,3/0,012	Walbro WT 99	H=1–1 1/4 L=1–1 1/4	0,80	8,4	1:1,36	M12x1,75	20,0	200-300	30°	9.190
250RX	48,7	44,0	32,0	2,4 (3,2) 9.200	2.700	4.300	13.500	Champion RCJ 7Y	0,5/0,02	Electrolux ET	0,3/0,012	Walbro HDA 86B Walbro HDA 142	H=1–1 1/4 L=1–1 1/4	0,80	8,9	1:1,36	M12x1,75	20,0	200-300	30°	9.930
252RX	50,8	45,0	32,0	2,4 (3,2) 9.000	2.700	4.300	14.000	Champion RCJ 7Y	0,5/0,02	Electrolux ET	0,3/0,012	Walbro HDA 142	H=1–1 1/4 L=1–1 1/4	0,80	8,9	1:1,36	M12x1,75	20,0	200-300	30°	10.300
265RX	65,1	48,0	36,0	2,98 (4,0) 8.400	2.250	3.500	11.500	Champion RCJ 7Y	0,5/0,02	SEM GA6 CD	0,3/0,012	Tillotson HS 121A	H=1–1 1/4 L=1–1 1/4	1,00	10,8	1:1,26	M12x1,75	20,0	200-300	25°	9.120
240RBD	36,3	38,0	32,0	1,3 (1,7) 9.000	2.700	3.600	11.000-12.000	Champion RCJ 7Y	0,5/0,02	Phelon CD	0,3/0,012	Walbro WT 235 Walbro WT 270	H=1–1 1/4 L=1–1 1/4	0,60	9,0	1:1,40	M10x1,25	20,0	200-300	35°	7.800
235P	36,3	38,0	32,0	1,3 (1,7) 9.000	2.700	3.900	_	Champion RCJ 7Y	0,5/0,02	Walbro CD	0,3/0,012	Walbro WT 235 Walbro WT 270	H=3/4–1 L=3/4–1	0,50	7,7	_	_	_	_	_	_
250PS	48,7	44,0	32,0	2,1 (2,8) 9.500	2.500	4.300	11.500	Champion RCJ 7Y	0,5/0,02	Electrolux ET	0,3/0,012	Walbro HDA 86B Walbro HDA 142	H=1–1 1/4 L=1–1 1/4	0,90	7,0	_	_	_	_	_	_
225E	25,4	34,0	28,0	0,9 (1,2) 9.000	2.700	3.700	11.000-12.000	Champion RCJ 7Y	0,5/0,02	Walbro CD	0,3/0,012	Walbro WT 270	H=1–1 1/4 L=1–1 1/4	0,50	6,1	1:1,40	M10x1,25	20,0	_	35°	8.500
18H	18,0	29,5	26,4	0,3 (0,4) 7.000	3.000	4.600	10.000	Champion RCJ 8Y	0,5/0,02	Phelon Solid State	0,3/0,012	Walbro WT 379 Zama C1U-W4	H=2 L=2	0,21	4,4	1:5,7	_	_	_	_	_
225H 60/75	25,4	34,0	28,0	0,9 (1,2) 9.000	2.700	5.400	11.000-12.000	Champion RCJ 7Y	0,5/0,02	Walbro CD	0,3/0,012	Walbro WT 406 Walbro WT 421	H=1–1 1/4 L=1–1 1/4	0,40	5,3 (60) 5,5 (75)	1:7,25	_	_	_	_	_

106 23 62-64

◊ Do not exceed the max no load free speed or engine damage may occur. This figure is for a broken in unit. Reduce RPM by 600-700 rpm for a new product.

* Basic setting only. Applies to needles without caps fitted

Husqvarna Forest & Garden 1997

www.mymowerparts.com