

ENGLISH

?

Please do not return unit to retailer. Por favor, no devuelva el aparato al lugar de compra. Veuillez ne pas retourner l'outil au détaillant. **1-800-554-6723** www.weedeater.com

> Operator's Manual Manual del Operador Manuel de L'utilisateur

# TWIST-N-EDGE TE 400 CXL

ESPAÑOL



# For Occasional Use Only



# WARNING:

Read and follow all Safety Rules and Operating Instructions before using this product. Failure to do so can result in serious injury.

# ADVERTENCIA:

Lea el manual del operador y siga todas las advertencias e instrucciones de seguridad. El no hacerlo puede resultar en lesiones graves.

# AVERTISSEMENT:

Lire le manuel de l'utilisateur et bien respecter tous les avertissements et toutes les instructions de sécurité. Tout défaut de le faire pourrait entraîner des blessures graves.

Electrolux Home Products North America Div. of WCI Outdoor Products, Inc. Augusta, GA 30907 Electrolux Home Products North America Div. of WCI Outdoor Products, Inc. Mississauga, Ontario 15T 1K6

Copyright ©2000 WCI Outdoor Products, Inc.

**530088895** 11/13/00

FRANÇAIS

# SAFETY RULES

**WARNING:** When using gardening appliances, basic safety precautions should always be followed to reduce the risk of fire and serious injury. Read and follow all instructions.

This power unit can be dangerous! Operator is responsible for following unit and manual instructions and warnings. Read entire Operator's Manual before using unit! Be thoroughly familiar with the controls and the proper use of the unit. Restrict the use of this unit to persons who read, understand, and follow unit and manual instructions and warnings. Never allow children to operate this unit.





OPERATORS MANUAL

SAFETY INFORMATION ON THE UNIT

**DANGER:** Never use blades, wire or flailing devices. This unit is designed for line trimmer use only. Use of any other accessories or attachments will increase the risk of injury



WARNING: Trimmer line throws objects violently. You and others can be blinded/ injured. Wear safety glasses and leg protection. Keep body parts clear of rotating line.

# Safety Glasses or similar eye protection Hazard Zone 50 ft. Boots (15 m)

Keep children, bystanders, and animals 50 feet (15 meters) away. If approached stop unit immediately.

If situations occur which are not covered in this manual, use care and good judgement. If you need Authorized need assistance, contact your Service Dealer call or 1-800-554-6723.

#### **OPERATOR SAFETY**

 Dress properly. Always wear safety glasses or similar eye protection when operating, or performing maintenance, on your unit (safety glasses are available). Eye protection should meet the require-ments of ANSI Z87.1.

- · Always wear face or dust mask if operation is dusty.
- Always wear heavy, long pants, long sleeves, boots, and gloves. Wearing safety leg guards is recommended.
- Always wear foot protection. Do not go barefoot or wear sandals. Stay clear of spinning line.
- Secure hair above shoulder length. Secure or remove loose clothing or clothing with loosely hanging ties, straps, tassels, etc. They can be caught in moving parts.
- Being fully covered also helps protect you from debris and pieces of toxic plants thrown by spinning line. Stay Alert. Do not operate this unit when
- you are tired, ill, upset, or under the influ-ence of alcohol, drugs, or medication.
- Wear hearing protection.
- Never start or run inside a closed room or
- building. Breathing exhaust fumes can kill.Keep handles free of oil and fuel.

# UNIT / MAINTENANCE SAFETY

- Disconnect the spark plug before perform-ing maintenance (except carburetor adjustments).
- · Look for and replace damaged or loose parts before each use. Look for and repair fuel leaks before use. Keep in good working condition.
- Replace trimmer head parts that are chipped, cracked, broken, or damaged in any other way before using the unit.
- Maintain unit according to recommended procedures. Keep cutting line at proper length.
- Use only 0.080" (2 mm) diameter Poulan/ Weed Eater® brand line. Never use wire, rope, string, etc.
- Install required shield properly before using the unit. Use only specified trimmer head; make sure it is properly installed and securely fastened.
- Make sure unit is assembled correctly as shown in this manual.
- Make carburetor adjustments with lower end supported to prevent line from contacting any object.
- Keep others away when making carburetor adjustments.
- Use only recommended Poulan/Weed Eater® accessories and replacement parts.
- · Have all maintenance and service not explained in this manual performed by an authorized service dealer.

#### **FUEL SAFETY**

- Mix and pour fuel outdoors.
- Keep away from sparks or flames.
- Use a container approved for fuel.
- Do not smoke or allow smoking near fuel or the unit.
- · Avoid spilling fuel or oil. Wipe up all fuel spills.
- Move at least 10 feet (3 meters) away from fueling site before starting engine.
- Stop engine and allow to cool before removing fuel cap.



# For Parts Call K&T 606-678-9623 or 606-561-4983

· Always store gasoline in a container approved for flammable liquids.

## **CUTTING SAFETY**

WARNING: Inspect the area before each use. Remove objects (rocks, broken glass, nails, wire, etc.) which can be thrown by or become entangled in line. Hard objects can damage trimmer head and be thrown causing serious injury.

- · Use only for trimming, mowing, edging and sweeping. Do not use for pruning or hedge trimming.
- Keep firm footing and balance. Do not overreach.
- Keep all parts of your body away from spinning line and muffler. Keep engine below waist level. A hot muffler can cause serious burns.
- · Cutting with the line on left side of the shield will throw debris away from the operator. • Use only in daylight or good artificial light.

## TRANSPORTING AND STORAGE

- · Allow the engine to cool; secure unit before storing or transporting in vehicle.
- Empty the fuel tank before storing or transporting the unit. Use up fuel left in the carburetor by starting the engine and letting it run until it stops.
- · Store unit and fuel in an area where fuel vapors cannot reach sparks or open flames from water heaters, electric motors or switches, furnaces, etc.
- Store unit so line limiter cannot accidentally cause injury. Unit can be hung by the tube.
- Store the unit out of the reach of children. If situations occur which are not covered in this manual, use care and good judgment. If you need assistance, call 1-800-554-6723.

SAFETY NOTICE: Exposure to vibrations through prolonged use of gasoline powered hand tools could cause blood vessel or nerve damage in the fingers, hands, and joints of people prone to circulation disorders or abnormal swellings. Prolonged use in cold weather has been linked to blood vessel damage in otherwise healthy people. If symptoms occur such as numbness, pain, loss of strength, change in skin color or texture, or loss of feeling in the fingers, hands, or joints, discontinue the use of this tool and seek medical attention. An anti-vibration system does not guarantee the avoidance of these problems. Users who operate power tools on a continual and regular basis must monitor closely their physical condition and the condi-

SPECIAL NOTICE: This unit is equipped with a temperature limiting muffler and spark arresting screen which meets the require-ments of California Codes 4442 and 4443. All U.S. forest land and the states of California, Idaho, Maine, Minnesota, New Jersey, Oregon, and Washington require by law that many internal combustion engines be

tion of this tool.

equipped with a spark arresting screen. If you operate in a locale where such regulations exist, you are legally responsible for maintaining the operating condition of these parts. Failure to do so is a violation of the law. For normal homeowner use, the muffler and spark arresting screen will not require any service. After 50 hours of use, we recommend that your muffler be serviced or replaced by your Authorized Service Dealer.

# ASSEMBLY

**WARNING:** Make sure your unit is properly assembled and all fasteners are secure.

#### ATTACHING THE HANDLE



· Assemble handle to the unit as shown; make sure bottom of handle is seated in the groove in the trigger housing.

NOTE: Wing nut must be assembled on the side of the unit opposite the operator's position.

· Pivot handle to a comfortable position. Tighten handle securely.

#### ATTACHING THE SHIELD

**WARNING:** The shield must be properly installed. The shield provides partial protection from the risk of thrown objects to the operator and others and is equipped with a line limiter blade which cuts excess line to the proper length. The line limiter blade (on underside of shield) is sharp and can cut you. Remove wing nut from shield.

- Insert bracket into slot as shown.
- Pivot shield until bolt passes through hole
- in bracket. Securely tighten wing nut onto bolt.



# FUEL YOUR UNIT

This engine is certified to operate on unleaded gasoline. Gasoline must be mixed with a good quality 2-cycle air-cooled engine oil designed to be mixed at a ratio of 40:1. Poulan/Weed Eater® brand oil is recommended. (A 40:1 ratio is obtained by mixing 3.2 ounces of oil with 1 gallon of unleaded gasoline). When mixing fuel follow the instructions printed on the container. Always read and follow the safety rules under FUÉL SAFETY.

# STARTING



#### HOW TO STOP YOUR UNIT

To stop engine, move ON/OFF switch to the OFF position.



## HOW TO START YOUR UNIT

**WARNING:** The trimmer head will turn while starting the engine. A hot muffler can cause serious burns.

#### STARTING A COLD ENGINE (or a warm engine after running out of fuel)

- Set unit on a flat surface.
- Move ON/OFF switch to the ON position.
- Slowly press the primer bulb 6 times.
- Move choke lever to FULL CHOKE position.
- · Squeeze the throttle trigger fully and hold through all remaining steps.
- Pull starter rope handle sharply 6 times. Move choke lever to HALF CHOKE posi-
- tion
- Pull starter rope handle no more than 6 pulls, until engine runs.
- Allow engine to run 10 seconds, then move choke lever to OFF CHOKE position.

#### **RESTARTING A WARM ENGINE**

- Move ON/OFF switch to the ON position. Move choke lever to OFF CHOKE position.
- Pull starter rope handle until engine runs.

 If engine does not start in 5 pulls, follow instructions in STARTING A COLD EN-GINE



## **OPERATING POSITION**



Cut from your right to your left.

## TRIMMER LINE ADVANCE

The cutting head advances line automatically. Do not tap head on the ground to advance line. This may break parts and cause cutting head to malfunction.

Upon unit start up, the line will advance auto-matically to the correct cutting path length. Always keep the shield in place when the tool is being operated.

#### **TWIST-N-EDGE**

- Pull the tab toward the engine. Twist the tube to the edging position;
- release the tab.



## **REPLACING THE LINE**

Pre-wound spools offer the most convenient method for replacing line and ensuring optimum performance.

 Replacement spools are color-coded to ensure use of the correct spool with your unit. Be sure to use the same color spool as the existing spool.

NOTE: Always clear dirt and debris from cutting head components when performing any type of maintenance.

- · Hold spool and unscrew cap by turning in the direction shown on top of the cap.
- · Remove line guide ring and spool. Line guide ring

Cap



• Use a pre-wound spool or refill spool with line. If using a pre-wound spool, remove tape strip from line and spool.



## **REFILLING THE SPOOL WITH LINE**

WARNING: Use only 0.080" (2 mm) diameter round line. Other sizes and shapes of line will not advance properly and will result in improper cutting head function or can cause serious injury. Do not use other materials such as wire, string, rope, etc. Wire can break off during cutting and become a dangerous missile that can cause serious injury.

 Cut a length of 30 feet of 0.080" (2 mm) diameter round Poulan/Weed Eater® brand line.



- Insert one end of line into center cavity of empty spool. Ensure line will feed into spool in the direction shown on the spool (counterclockwise).
- Continue feeding line into spool, leaving 4 6 inches (10 – 15 cm) unwound from center of spool.

#### **INSTALLING SPOOL WITH LINE**

- · Install replacement spool.
- Thread line through line guide ring.

Line through guide ring



#### Replacement Spool

- Rest guide ring on spool and place line in slot. Allow line to extend 4 - 6 inches (10 -15 cm) from center of spool.
- Ensure line remains in slot while screwing cap on to the shaft. Only tighten cap hand tight!

# SERVICE

We recommend all service and adjustments not listed in this manual be performed by an Authorized Service Dealer.

#### CARBURETOR ADJUSTMENTS

Your carburetor is equipped with limiter caps. Carburetor adjustment is a complicated task. We recommend that you take your unit to an Authorized Service Dealer. Damage will occur if you turn the needles beyond the limiter stops.

## **IGNITION TIMING**

The ignition timing is fixed, non-adjustable. **SPARK PLUG** 

Replace the spark plug yearly using a Champion RCJ-8Y plug. Spark plug gap is 0.025".

# **NEED ASSISTANCE?**

Need Assistance? Call 1-800-554-6723. Need Service Parts? Contact your dealer .

## TROUBLESHOOTING TABLE

A WARNING: Always stop unit and disconnect spark plug before performing any of the

| recommended remedies below other than remedies that require operation of the unit. |   |  |
|--|---|--|
| TROUBLE  | CAUSE   | REMEDY   |
| Engine will not<br>start.  | <ul> <li>Engine flooded.</li> <li>Fuel tank empty.</li> <li>Spark plug not firing.</li> <li>Fuel not reaching carburetor.</li> <li>Carburetor requires adjustment.</li> </ul> | <ul> <li>See "Starting."</li> <li>Fill tank with correct fuel mixture.</li> <li>Install new spark plug.</li> <li>Check for dirty fuel filter; replace.<br/>Check for kinked or split fuel line;<br/>repair or replace.</li> <li>See "Carburetor Adjustments."</li> </ul> |
| Engine will not idle properly.   | <ul> <li>Carburetor requires adjustment.</li> <li>Throttle trigger screw too tight.</li> </ul>  | <ul> <li>See "Carburetor Adjustments."</li> <li>Loosen screw.</li> </ul>   |
| Engine will not<br>accelerate,<br>lacks power,<br>or dies under<br>a load.         | <ul> <li>Air filter dirty.</li> <li>Spark plug fouled.</li> <li>Carburetor requires adjustment.</li> </ul>  | <ul> <li>Clean or replace air filter.</li> <li>Clean or replace spark plug; re-gap.</li> <li>See "Carburetor Adjustments."</li> </ul>  |
| Engine<br>smokes<br>excessively.   | <ul> <li>Fuel mixture incorrect.</li> <li>Air filter dirty.</li> <li>Carburetor requires adjustment.</li> </ul>   | <ul> <li>Empty fuel tank and refill with correct fuel mixture.</li> <li>Clean or replace air filter.</li> <li>See "Carburetor Adjustments."</li> </ul>   |
| Line does not<br>advance or<br>breaks while<br>cutting.                            | <ul> <li>Line improperly routed in head.</li> <li>Line improperly routed through<br/>line guide.</li> <li>Line size incorrect.</li> </ul>                                     | <ul> <li>Check line routing.</li> <li>See "Replacing the line."</li> <li>Use only 0.080" (2 mm) dia. line.</li> </ul>  |
| Line welds<br>onto spool.  | <ul> <li>Line size incorrect.</li> <li>Incorrect spool.</li> <li>Line is being crowded against<br/>material being cut.</li> </ul>   | <ul> <li>Use only 0.080" (2 mm) dia. line.</li> <li>Replace with correct spool.</li> <li>Cut with tip of line fully extended.</li> </ul>   |
| Line pulls<br>back into<br>head.   | <ul><li>Too little line outside of head.</li><li>Line size incorrect.</li></ul>   | <ul> <li>Remove spool and pull 4 - 6 inches<br/>(10 - 15 cm) of line outside of head.</li> <li>Use only 0.080" (2 mm) dia. line.</li> </ul>  |

# LIMITED WARRANTY

ELECTROLUX HOME PRODUCTS NORTH AMERICA, Division of WCI Outdoor Products, Inc. warrants to the original purchaser that each new Weed Eater brand gasoline tool or attachment is free from defects in material and workmanship and agrees to repair or replace under this warranty any defective gasoline product or attachment as follows from the original date of purchase. 2 YEARS- Parts and Labor, when used for

2 YEARS - Parts and Labor, when used for household purposes. 90 DAYS - Parts and Labor, when used for

**90 DAYS** - Parts and Labor, when used for commercial, professional, or income producing purposes.

**30 DAYS -** Parts and Labor, if used for rental purposes.

This warranty is not transferable and does not cover damage or liability caused by improper handling, improper maintenance, or the use of accessories and/or attachments not specifically recommended by **ELECTROLUX HOME PRODUCTS NORTH AMERICA** for this tool. Additionally, this warranty does not cover tuneups, spark plugs, filters, starter ropes, starter springs, cutting line, or rotating head parts that will wear and require replacement with reasonable use during the warranty period. This warranty does not cover predelivery setup or normal adjustments explained in the operator's manual.

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE. NO CLAIMS FOR CONSEQUENTIAL OR OTHER DAMAGES WILL BE ALLOWED, AND THERE ARE NO OTHER EXPRESS WARRANTIES EXCEPT THOSE EX-PRESSLY STIPULATED HEREIN. SOME STATES DO NOT ALLOW LIMITA-TIONS ON HOW LONG AN IMPLIED WAR-

RANTY LASTS OR THE EXCLUSION OR LIMITATIONS OF INCIDENTAL OR CONSE-QUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS OR EXCLUSION MAY NOT APPLY TO YOU.

ELECTROLUX HOME PRODUCTS NORTH AMERICA'S policy is to continuously improve its products. Therefore, ELECTROLUX HOME PRODUCTS NORTH AMERICA reserves the right to change modify or discontinue models

right to change, modify, or discontinue models, designs, specifications, and accessories of all products at any time without notice or obligation to any purchaser.

# U.S. EPA / ENVIRONMENT CANADA EMISSION CONTROL WARRANTY STATEMENT

YOUR WARRANTY RIGHTS AND OB-LIGATIONS: The U. S. Environmental Protection Agency/Environment Canada and POULAN/WEED EATER, DIVISION OF WCI OUTDOOR PRODUCTS are pleased to explain the emissions control system warranty on your lawn and garden equipment engine. All new utility and lawn and garden equipment All new utility and lawn ano gargen equipment engines must be designed, built, and equipped to meet the stringent anti-smog standards. POULAN/WEED EATER must warrant the emission control system on your lawn and garden equipment engine for the periods of time listed below provided there has been no abuse, neglect, or improper maintenance of your lawn and garden equipment engine. Your emission control system includes parts such as the carburetor and the ignition system. Where a warrantable condition exits, POULAN/WEED EATER will repair your lawn and garden equipment engine at no cost to you. Expenses covered under warranty include diagnosis, parts and labor. MANUFAC-TURER'S WARRANTY COVERAGE: If any emissions related part on your engine (as listed under Emissions Control Warranty Parts List) is defective or a defect in the materials or workmanship of the engine causes the failure of such an emission related part, the part will be repaired or replaced by POULAN WEED EATER. OWNER'S WARRANTY RESPONSIBILITIES: As the lawn and garden equipment engine owner, you are re-sponsible for the performance of the required maintenance listed in your Owner's Manual. POULAN/WEED EATER recommends that you retain all receipts covering maintenance on your lawn and garden equipment engine, but POULAN/WEED EATER cannot deny warranty solely for the lack of receipts or for your failure to ensure the performance of all scheduled maintenance. As the lawn and garden equipment engine owner, you should be aware that POULAN/WEED EATER may deny you warranty coverage if your lawn and garden equipment engine or a part of it has failed due to abuse, neglect, improper mainte-nance, unapproved modifications, or the use of parts not made or approved by the original equipment manufacturer. You are responsi-ble for presenting your lawn and garden equipment engine to a POULAN/WEED EAT-ER authorized repair center as soon as a problem exists. Warranty repairs should be completed in a reasonable amount of time, not to exceed 30 days. If you have any questions regarding your warranty rights and responsibilities, you should contact your nearest authorized service center or call POULAN/WEED EATER at 1-800-554-6723. WARRANTY COM-MENCEMENT DATE: The warranty period begins on the date the lawn and garden equip-

ment engine is purchased. LENGTH OF COVERAGE: This warranty shall be for a period of two years from the initial date of pur-chase. WHAT IS COVERED: REPAIR OR REPLACEMENT OF PARTS. Repair or replacement of any warranted part will be per-formed at no charge to the owner at an approved POULAN/WEED EATER servicing center. If you have any questions regarding your warranty rights and responsibilities, you should contact your nearest authorized ser-vice center or call POULAN/WEED EATER at WARRANTY PERIOD: 1-800-554-6723 Any warranted part which is not scheduled for replacement as required maintenance, or which is scheduled only for regular inspection to the effect of "repair or replace as necessary" shall be warranted for 2 years. Any warranted part which is scheduled for replacement as required maintenance shall be warranted for the period of time up to the first scheduled replacement point for that part. **DIAGNOSIS:** The owner shall not be charged for diagnostic labor which leads to the determination that a warranted part is defective if the diagnostic work is performed at an approved POULAN/WEED E ATER servicing center. CONSEQUENTIAL DAM-AGES: POULAN/WEED EATER may be liable for damages to other engine components caused by the failure of a warranted part still under warranty. WHAT IS NOT COVERED: All failures caused by abuse, neglect, or improper maintenance are not covered. ADD-ON OR MODIFIED PARTS: The use of add-on or modified parts can be grounds for disallowing a warranty claim. POULAN/WEED EATER is not liable to cover failures of warranted parts caused by the use of add-on or modified parts. HOW TO FILE A CLAIM: If you have any questions regarding your warranty rights and responsibilities, you should contact your nearest authorized ser-vice center or call POULAN/WEED EATER at 1-800-554-6723. WHERE TO GET WAR-RANTY SERVICE: Warranty services or repairs shall be provided at all POULAN/WEED ATER service centers. call: 1-800 MAINTENANCE, REPLACEMENT AND RE-PAIR OF EMISSION RELATED PARTS: Any POULAN/WEED EATER approved replacement part used in the performance of any warranty maintenance or repair on emission related parts will be provided without charge to the owner if the part is under warranty. EMIS-SION CONTROL WARRANTY PARTS LIST: Carburetor, Ignition System: Spark Plug (covered up to maintenance schedule), Ignition Module. **MAINTENANCE STATE**-**MENT:** The owner is responsible for the performance of all required maintenance as defined in the owner's manual.

The information on the product label indicates which standard your engine is certified. Example: (Year) EPA Phase 1 or Phase 2 and/or CALIFORNIA.



8

www.mymowerparts.com